



◆ストレート形

RoHS 指令対応品

規格	呼び		各部の寸法								標準色	適合電線範囲		適合工具	一箱入数	
	ビニル	ナイロン	d	B	φd	F ₁	L ₁	L ₂	L	L ₃		板厚	絶縁φ			AWG
	AVF0.08-3	-	3.2	5.2	2.2	5.9	9.5	12.5	18.0		0.8	黄	0.08	28	DS05N DH-1B	1,000 (100×10)
	AVF0.08-V3.5	-	3.7	5.7		7.7		15.0	20.5							
◎	AVF0.3-2	-	2.2	5.2		5.9		12.5	18.0							
◎	AVF0.3-3	-	3.2	5.2		5.9		12.5	18.0							
	AVF0.3-V3.5	-		5.7	2.2	7.7	9.5				0.65	黄	0.1 ∩ 0.3	26-22	*DS05N *DH-1B *DS-A5	1,000 (100×10)
	AVF0.3-L3.5	-	3.7	5.7		6.7		15.0	20.5							
◎	AVF0.3-3.5	-	4.3	6.6		7.7										
◎	AVF0.3-4	-		6.6												
◎	AVF0.5-2	APF0.5-2	2.2	5.2		5.9		12.5	18.0							
◎	AVF0.5-3	APF0.5-3	3.2	5.2		5.9		12.5	18.0							
	AVF0.5-V3.5	APF0.5-V3.5		5.7	2.2	7.7	9.5				0.5	黄	0.3 ∩ 0.5	22-20	*DS05N *DH-1B *DS-A5	1,000 (100×10)
	AVF0.5-L3.5	APF0.5-L3.5	3.7	5.7		6.7		15.0	20.5							
◎	AVF0.5-3.5	APF0.5-3.5		6.6		7.7										
◎	AVF0.5-4	APF0.5-4	4.3	6.6		7.7										
◎	AVF0.5-5	APF0.5-5	5.3	8.0		7.0										
◎	AVF1.25-M3	APF1.25-M3		5.6		5.0		14.2	19.2							
◎	AVF1.25-3	APF1.25-3		6.0		4.4		14.2	19.2							
	AVF1.25-V3	APF1.25-V3	3.2	5.7		6.3		15.2	20.2							
◎	AVF1.25-L3	APF1.25-L3		5.9		6.5		15.6	20.6							
◎	AVF1.25-C3.5	APF1.25-C3.5		6.0		4.5		12.8	17.8							
◎	AVF1.25-S3.5	APF1.25-S3.5		5.7		6.3		13.5	18.5							
◎	AVF1.25-3.5	APF1.25-3.5		6.0		4.4		14.2	19.2							
◎	AVF1.25-V3.5	APF1.25-V3.5	3.7	5.7	3.3	6.3	9.5	15.2	20.2		0.8	赤	∩	20-16	*DS-H3 *DS-H3M *DS-H3MS *DH-1B *DS-A5	500 (100×5)
◎	AVF1.25-L3.5	APF1.25-L3.5		5.9		6.5		15.6	20.6							
◎	AVF1.25-A3.5	APF1.25-A3.5		6.4		6.5		15.4	20.4				1.65			
◎	AVF1.25-S4	APF1.25-S4		6.4		6.8		15.6	20.6							
◎	AVF1.25-4	APF1.25-4	4.3	7.0		6.5		16.2	21.2							
◎	AVF1.25-A4	APF1.25-A4		8.3		7.1		16.2	21.2							
◎	AVF1.25-5	APF1.25-5	5.3	8.0		7.0		16.8	21.8							
◎	AVF1.25-6	APF1.25-6	6.4	9.7		7.6		17.0	22.0							
◎	AVF2-3	APF2-3		5.5		4.4		14.2	19.2							
	AVF2-A3	APF2-A3	3.2	5.7		6.1		14.2	19.2							
◎	AVF2-S3.5	APF2-S3.5		5.7		6.5		15.7	20.7							
◎	AVF2-3.5	APF2-3.5	3.7	6.5		6.0		15.8	20.8				1.04	16-14	*DS-H4 *DS-H3M *DS-H3MS *DH-1B *DS-A5	500 (100×5)
◎	AVF2-M4	APF2-M4		6.4		6.7		15.6	20.6							
◎	AVF2-S4	APF2-S4		6.6		8.0		15.8	20.8							
◎	AVF2-4	APF2-4	4.3	6.9		7.2		16.2	21.2				2.63			
◎	AVF2-A4	APF2-A4		8.3												
◎	AVF2-5	APF2-5	5.3	8.5		8.5		17.2	22.2							
◎	AVF2-6	APF2-6	6.4	11.0		9.5		20.2	25.2							400 (100×4)
◎	AVF3.5-4	APF3.5-4	4.3	8.0	4.9	7.5	14.0	17.8	26.5		1.0	黄	2.63 ∩ 4.6	12		300 (100×3)
◎	AVF3.5-5	APF3.5-5	5.3	8.0												
◎	AVF5.5-M4	APF5.5-M4		7.1		7.9		19.5	27.2							
◎	AVF5.5-4	APF5.5-4	4.3	8.5		7.2		18.0	25.7							
◎	AVF5.5-5	APF5.5-5	5.3	9.0	5.4	8.5	14.0	19.0	26.7		1.0	黄	2.63 ∩ 6.64	12-10	*DS-H5 *DH-1B *DS-A5	300 (100×3)
◎	AVF5.5-6	APF5.5-6	6.4	12.5				23.5	31.2							
◎	AVF5.5-8	APF5.5-8	8.4	15.0		10.5		24.5	32.2							200 (100×2)

1. 各呼びの印は、UL登録品、CSA登録品です。
2. CSA登録品としてご使用の際は、注文時にご指示ください。カートンがCSA品用となります。
3. 上記寸法表にかかわらず特注品もご相談ください。
4. *印はUL適合工具です。